



DELTA-X215

Dual 15" passive with bi-amp functionality

Product Description

Delta-X215 is a quasi 3-way passive loudspeaker built for large-scale sound reinforcement where power and authority are critical.

Made from 18 mm birch plywood and finished in our durable Tough-Tone paint, the cabinet is road-ready and resilient while keeping a professional look for any stage or install.

With dual 15-inch Wharfedale Pro custom LF drivers handling the low frequencies, the X215 delivers immense bass weight and projection. Its dedicated MF/HF section adds definition and clarity through the midrange and crisp, articulate highs across wide coverage.

Rated at 1,000 W continuous (up to 4,000 W peak) and capable of producing 137 dB SPL, it has the headroom to fill demanding spaces with confidence.

The rear panel switch allows full-range passive operation or bi-amp mode for precise system tuning.

Equipped with side handles and rigging points, the Delta-X215 combines huge output with practical deployment for touring or fixed installations.

Key Features

- ✓ Full-Range, Quasi 3-way
- ✓ 2 x 15" LF Driver
- ✓ 1000 W Continuous
- ✓ 137 dB Max SPL @ 1m
- ✓ 4 Ω Impedance
- ✓ 2000 W Programme



Specifications

Specification	Value
Active / Passive	Passive
System Type	Full-Range
Configuration	Quasi 3-way
System Continuous Power	1000 W
System Programme Power	2000 W
System Peak Power	4000 W
Max SPL @ 1m	137 dB
Sensitivity 2.83 V / 1 m	101 dB
Frequency Response (+/-3dB)	45 Hz - 20 kHz
Frequency Range (-10dB)	40 Hz - 20 kHz
Crossover Frequency	630 Hz - 1.8 kHz
Bluetooth	No
Input Connector	2 x 4 Pole Speaker Connector
LF Driver Size	2 x 15"
LF Voice Coil Size	3"
LF Rated Impedance	8 Ω
LF Power (RE:AES2-2012)	2 x 500 W
HF Driver Type	Compression Driver
HF Voice Coil Size	2"
HF Diaphragm Material	1.4"
HF Power (RE:AES2-2012)	50 W
HF Rated Impedance	8 Ω
Nominal Coverage (H x V)	90° x 45°
EQ Type	None

Specifications (continued)

Specification	Value
Enclosure Material	Birch Plywood
Grille Material and Finish	Steel Black
Finish	Black Tough-Tone
Handles	3
Deployment	Ground
Pole Mount	None
Brackets Included	No
Rigging	No
Included Accessory	User Manual, 2 x Castor Wheels
Unpacked Height	1135 mm
Unpacked Width	488 mm
Unpacked Rear	300 mm
Unpacked Depth	450 mm
Packed - Height	1230 mm
Packed - Width Front	520 mm
Packed - Width Rear	520 mm
Packed - Depth	565 mm
Net Weight	51.84 kg
Gross Weight	59.82 kg