



DELTA-X212

Dual 12" passive with bi-amp functionality

Product Description

Delta-X212 is a quasi 3-way passive loudspeaker designed for high-power applications where clarity, coverage and authority are essential.

Constructed from 18 mm birch plywood and coated in our Tough-Tone paint, it's rugged enough for touring and fixed installations while maintaining a professional finish.

Its dual 12-inch custom Wharfedale Pro LF drivers work in tandem with a dedicated MF/HF section, producing powerful, controlled low-end with natural, defined mids and crisp high-frequency detail.

Handling 800 W continuous (up to 3,200 W peak) and reaching a maximum SPL of 135 dB, the Delta-X212 delivers impressive volume without sacrificing accuracy. The rear panel provides a choice of passive or bi-amp operation, giving system engineers flexibility to match their setup.

With robust side handles and rigging points, the Delta-X212 is a practical, professional solution for venues and events needing full-range impact with real finesse.

Key Features

- | | |
|---------------------------|------------------------|
| ✓ Full-Range, Quasi 3-way | ✓ 135 dB Max SPL @ 1m |
| ✓ 2 x 12" LF Driver | ✓ 4 Ω Impedance |
| ✓ 800 W Continuous | ✓ 1600 W Programme |



Specifications

Specification	Value
Active / Passive	Passive
System Type	Full-Range
Configuration	Quasi 3-way
System Continuous Power	800 W
System Programme Power	1600 W
System Peak Power	3200 W
Max SPL @ 1m	135 dB
Sensitivity 2.83 V / 1 m	100 dB
Frequency Response (+/-3dB)	53 Hz - 20 kHz
Frequency Range (-10dB)	45 Hz - 20 kHz
Crossover Frequency	1.8 kHz
Bluetooth	No
Input Connector	2 x 4 Pole Speaker Connector
LF Driver Size	2 x 12"
LF Voice Coil Size	2"
LF Rated Impedance	8 Ω
LF Power (RE:AES2-2012)	2 x 400 W
HF Driver Type	Compression Driver
HF Voice Coil Size	2"
HF Diaphragm Material	1.4"
HF Power (RE:AES2-2012)	50 W
HF Rated Impedance	8 Ω
Nominal Coverage (H x V)	90° x 45°
EQ Type	None

Specifications (continued)

Specification	Value
Enclosure Material	Birch Plywood
Grille Material and Finish	Steel Black
Finish	Black Tough-Tone
Handles	2
Deployment	Ground
Pole Mount	None
Brackets Included	No
Rigging	No
Included Accessory	User Manual
Unpacked Height	964 mm
Unpacked Width	390 mm
Unpacked Rear	242 mm
Unpacked Depth	373 mm
Packed - Height	1080 mm
Packed - Width Front	566 mm
Packed - Width Rear	566 mm
Packed - Depth	464 mm
Net Weight	38 kg
Gross Weight	45 kg