



i4

IP54 Certified Installation Loudspeakers

Product Description

i4 is a compact installation loudspeaker from our i Series, designed for distributed audio systems where clarity, reliability, and all-weather durability are essential.

Equipped with a 4.0" LF driver and 1.0" HF dome tweeter, i4 delivers articulate, full-range sound suitable for restaurants, retail spaces, offices, and public areas. Its IP54 certification ensures protection against dust and water spray, making it ideal for both indoor and semi-outdoor installations.

Constructed from ABS plastic with a full frontal steel grille, i4 is built to last while maintaining a clean, unobtrusive appearance. Each pair is supplied with fully adjustable mounting brackets, allowing flexible positioning thanks to their semi-circular "ball and socket" design. A seismic restraint tether attachment point is also included for secure installation.

Finished in black or white, i4 integrates seamlessly into any décor. Designed for 8 Ω operation, it features Phoenix connectors for secure, straightforward wiring and quick installation.

Key Features

- | | |
|---------------------|------------------------|
| ✓ Full-Range, 2-way | ✓ 105 dB Max SPL @ 1m |
| ✓ 4" LF Driver | ✓ 8 Ω Impedance |
| ✓ 25 W Continuous | ✓ 50 W Programme |



Specifications

Specification	Value
Active / Passive	Passive
System Type	Full-Range
Configuration	2-way
System Continuous Power	25 W
System Programme Power	50 W
System Peak Power	100 W
Max SPL @ 1m	105 dB
Sensitivity 2.83 V / 1 m	84 dB
Frequency Response (+/-3dB)	100 Hz - 20 kHz
Frequency Range (-10dB)	60 Hz - 20 kHz
Crossover Frequency	2.8 kHz
Bluetooth	No
Input Connector	Phoenix Terminal
LF Driver Size	4"
LF Voice Coil Size	1"
LF Rated Impedance	8 Ω
LF Power (RE:AES2-2012)	25 W
HF Driver Type	Soft Dome Tweeter
HF Voice Coil Size	1"
HF Power (RE:AES2-2012)	10 W
HF Rated Impedance	8 Ω
Nominal Coverage (H x V)	110° x 130°
Enclosure Material	ABS
Grille Material and Finish	Aluminium

Specifications (continued)

Specification	Value
Finish	Black or White
Handles	No
Deployment	Wall Mount
Pole Mount	None
Brackets Included	Yes
Rigging	No
Included Accessory	Wall Bracket, User Manual
Unpacked Height	232 mm
Unpacked Width	160 mm
Unpacked Rear	160 mm
Unpacked Depth	148 mm
Packed - Height	340 mm
Packed - Width Front	216 mm
Packed - Width Rear	216 mm
Packed - Depth	430 mm
Net Weight	4 kg
Gross Weight	5.4 kg