



i8

IP54 Certified Installation Loudspeakers

Product Description

i8 is an 8" installation loudspeaker from our i Series, engineered for distributed audio systems that require higher output, extended low-end response, and all-weather reliability.

Equipped with an 8.0" LF driver and 1.0" HF dome tweeter, i8 delivers powerful, balanced sound ideal for restaurants, bars, retail spaces, and commercial installations. Its IP54 certification protects against dust and water spray, ensuring consistent performance in both indoor and semi-outdoor environments.

Constructed from robust ABS plastic with a full frontal steel grille, i8 offers durability and a clean, professional appearance. Each pair includes fully adjustable mounting brackets featuring a semi-circular "ball and socket" design for precise aiming and secure installation, along with a seismic restraint tether attachment point for added safety.

Finished in black or white, i8 integrates seamlessly into any décor. Designed for 8 Ω operation, it features Phoenix connectors for secure, straightforward wiring and quick installation.

Key Features

- | | |
|---------------------|------------------------|
| ✓ Full-Range, 2-way | ✓ 110 dB Max SPL @ 1m |
| ✓ 8" LF Driver | ✓ 8 Ω Impedance |
| ✓ 50 W Continuous | ✓ 100 W Programme |



Specifications

Specification	Value
Active / Passive	Passive
System Type	Full-Range
Configuration	2-way
System Continuous Power	50 W
System Programme Power	100 W
System Peak Power	200 W
Max SPL @ 1m	110 dB
Sensitivity 2.83 V / 1 m	87 dB
Frequency Response (+/-3dB)	70 Hz - 20 kHz
Frequency Range (-10dB)	50 Hz - 20 kHz
Crossover Frequency	2.0 kHz
Bluetooth	No
Input Connector	Phoenix Terminal
LF Driver Size	8"
LF Voice Coil Size	1"
LF Rated Impedance	8 Ω
LF Power (RE:AES2-2012)	50 W
HF Driver Type	Soft Dome Tweeter
HF Voice Coil Size	1"
HF Power (RE:AES2-2012)	10 W
HF Rated Impedance	8 Ω
Nominal Coverage (H x V)	130° x 180°
Enclosure Material	ABS
Grille Material and Finish	Aluminium

Specifications (continued)

Specification	Value
Finish	Black or White
Handles	No
Deployment	Wall Mount
Pole Mount	None
Brackets Included	Yes
Rigging	No
Included Accessory	Wall Bracket, User Manual
Unpacked Height	405 mm
Unpacked Width	270 mm
Unpacked Rear	270 mm
Unpacked Depth	234 mm
Packed - Height	560 mm
Packed - Width Front	360 mm
Packed - Width Rear	360 mm
Packed - Depth	600 mm
Net Weight	9.36 kg
Gross Weight	12.9 kg