



TITAN-12D

Legendary 12" Bi-amplified full range loudspeaker

Product Description

12" Bi-amplified active loudspeaker
300 w Continuous
600 w Peak
Bass Response Optimiser
24-Bit DSP Processing

Key Features

- | | |
|---------------------|--------------------|
| ✓ Full-Range, 2-way | ✓ dB Max SPL @ 1m |
| ✓ 12" LF Driver | ✓ 300 W Continuous |
| ✓ 600 W Peak | ✓ Polypropylene |



Specifications

Specification	Value
Active / Passive	Active
System Type	Full-Range
Configuration	2-way
System Continuous Power	300 W
System Peak Power	600 W
Frequency Response (+/-3dB)	55 Hz - 20 kHz
Crossover Frequency	2.3 kHz
Bluetooth	No
Input Connector	Combo Jack: 1/4" - XLR Summed Dual RCA Jacks
Link Connector	pin XLR
LF Driver Size	12"
HF Driver Type	Compression Driver
HF Diaphragm Material	1"
Nominal Coverage (H x V)	90° x 60°
Amplifier design	Class D
Input sensitivity	XLR - 1/4" Combo jack: 0dBu (-2.2dBv or 0.775Vrms) / RCA: 0dBu (-2.2dBv or 0.775Vrms)
Max Input Level	+22 dBu
Line output	Switchable LOOP/MIX Balanced socket XLR
Enclosure Material	Polypropylene
Grille Material and Finish	Steel Black
Finish	Black Polypropylene
Handles	2
Deployment	Flying, Ground, Pole, Wall Mount
Pole Mount	35 mm

Specifications (continued)

Specification	Value
Brackets Included	No
Rigging	Yes
M8	10
Main Power	AC100-120 V~/220-240 V~,50/60 Hz
Power Supply	High Efficiency Switching Mode Power Supply
Included Accessory	User Manual, AC Cable, Dust cover
Unpacked Depth	312 mm
Packed - Height	408 mm
Packed - Width Front	435 mm
Packed - Width Rear	435 mm
Packed - Depth	663 mm
Net Weight	12.44 kg
Gross Weight	15.78 kg